



**PRODUITS CHIMIQUES
SPECIAUX**

NEUTRAL DA 66

High performance neutralizer brightener for wood greyed by weather or cleaned by an alkaline remover.

I Applications:

This product is designed to brighten all types of wood blackened by weather or time and to neutralize after alkaline scouring.

II Product Advantages:

- Fast
- Can be sprayed
- Effective on all types of wood
- Can be repainted immediately
- Requires a light rinsing

III Physicochemical Properties:

- Fluoride salts based product in water phase
- Colourless transparent liquid
- Density: 1.05 g/cm³ at 20°C
- PH: 1
- Not frost resistant, but effects reversible
- Flash Point: Non-flammable

IV Instructions for use:

1. Dilution: Dilute in 50% of water or use pure according to the state of the surface.
2. Tools: Brush, natural fibre roller, sprayer (spray).
3. Method: Mix the product well. Permeate the surface to be treated. May also be used in a neutralizer brightener bath (stainless steel). After the operation wipe with a damp cloth.
4. Application Time: Results almost instantaneous.
5. Application Temperature: From 5 to 50°C. Efficacy is reduced at extreme temperatures.
6. Application Rate: Variable according to the type of wood (from 150 g to 300 g/m²).

V Precautions for Safe Handling & Use:

1. Protection of surfaces: do not apply to siliceous and limestone materials. Do not apply to glass.
2. Protection of personnel: Avoid contact with eyes and skin. In case of contact, wash hands and eyes immediately with water.

VI Cleaning of tools:

Clean tools in water immediately after use.

VII Packaging, palletising, storage:

- 20 kg: pallet of 24 X 20 kg
- 5 kg: carton of 4 X 5 kg
- 1 kg: carton of 12 units,

Important: The contents of this documentation result from our experience of the product. We cannot be held responsible for its use in each individual case. It is essential to test areas to be treated beforehand.

Scalp E49a

Created: February 1997/1166

Updated: April 2005



8 - 14, ALLÉE DE BRUXELLES - Z.I. DE LA POUDRETTE - 93320 PAVILLONS SOUS BOIS
TÉL. : 01 48 48 39 76 - FAX : 01 48 49 80 36 - E - mail : scalp@scalp-france.fr
S.A. AU CAPITAL DE 115 500 € - R.C. BOBIGNY B 582 112 227 - C.C.P. PARIS 2727-780 - SITE internet : www.scalp-france.fr