



**PRODUITS CHIMIQUES
SPECIAUX**

SCALP PIERRE BIO 89

New generation ecological cleaner for facades in stone, marble, thick and medium plasticized coatings, paint, lime-based hydraulic coatings, and in certain cases, exposed aggregate blocks, concretes, deactivated concrete.

I Applications:

Designed for the cleaning, washing and scouring of all mineral, organic surfaces hydraulic coatings, from blackening from atmospheric and urban pollution.

II Product Advantages:

- Not hazardous to health or the environment
- No surface neutralizing (no efflorescence)
- Contains no sodium carbonate, no acid; no solvents
- Significant financial savings on sandblasting and hydro cleaning (No need for on site safety operations, no need to clean sand. residues (Fast and effective technique).
- No special labelling required according to regulations in force, for use and transport
- Does not affect anodised aluminium, Altuglass, glass, or rubber, etc. (Tiles and windows do not need protection), Avoid prolonged contact with aluminium and do not let the product dry.
- Biodegradable
- Ecological
- Can be sprayed

III Physicochemical Properties:

- Aqueous product in thixotropic gel form
- Slightly yellowish
- Density: 1.10 g/cm³ at 20°C
- PH: 12
- Not frost resistant, but effects reversible
- Flash Point: Non-flammable

IV Instructions for use:

1. Dilution: Never dilute.
2. Tools: Roller, brush (all types), can be sprayed with an airless spray gun or sprayer.
3. Method: Mix the product well before use. Apply thickly to the surface then leave to act. Rinse from the base upwards with water under pressure (cold or hot). Renew the operation as necessary. Do not apply to facades in thawing conditions.
4. Application Time: One or several hours. We advise applying in the evening and rinsing the following day.
5. Application Temperature: From 5 to 50°C. Efficacy is reduced at extreme temperatures.
6. Application Rate: From 100 to 200 g/m² according to surface porosity.

V Precautions for Safe Handling & Use:

1. Protection of surfaces: No particular recommendation.
2. Protection of personnel: This product is not dangerous, but avoid contact with eyes and skin. In case of contact, wash with water.

VI Cleaning of tools:

Clean tools in water immediately after use.

VII Packaging, palletising, storage:

- 20 kg: pallet of 24 X 20 kg
- 5 kg: carton of 4 X 5 kg

Important: The contents of this documentation result from our experience of the product. We cannot be held responsible for its use in each individual case. It is essential to test areas to be treated beforehand.

SCALP E49a

Created: Mai1999/1289

Updated: 30/05/2005



8 - 14, ALLÉE DE BRUXELLES - Z.I. DE LA POUDRETTE - 93320 PAVILLONS SOUS BOIS
TÉL. : 01 48 48 39 76 - FAX : 01 48 49 80 36 - E - mail : scalp@scalp-france.fr
S.A. AU CAPITAL DE 115 500 € - R.C. BOBIGNY B 562 112 227 - C.C.P. PARIS 2727-780 - SITE internet : www.scalp-france.fr