



**PRODUITS CHIMIQUES
SPECIAUX**

SCALPEX G 6

High performance stripper for paint on polyurethane and epoxy floor coverings and all paint on metallic surfaces.

I Applications:

Scouring of highly polymerised paint where classic paint strippers do not work fully. Designed specifically to clean organic coatings used in the aeronautic, automotive, marine, mechanical and building industries.

II Product Advantages:

- Fast and effective on all organic surfaces
- Not of loss (total accessibility)
- Product can be used straight from container
- Approved 25 kg containers, opening totally to facilitate painter or operator's work
- Versatile product
- Stackable when empty (space saving)

III Physicochemical Properties:

- Methylene chloride based product.
- Slightly yellowish colour.
- Density: 1.24 g/cm³ at 20°C
- PH: 1.
- Frost resistant.
- Flash Point: Non-flammable.

IV Instructions for use:

- 1. Dilution:** Ready to use (never dilute).
- 2. Tools:** Low-pressure sprayer, roller, paintbrush, brush, possibly airless spray gun.
- 3. Method:** Apply in a thick layer and scrape with scraper or plastering knife. Rinse immediately with water under pressure. Avoid applying to wet surfaces.
- 4. Application Time:** About 20 minutes according to climatic conditions and coating. Never let the product dry.
- 5. Application Temperature:** From 5 to 50°C. Efficacy is reduced at extreme temperatures.
- 6. Application Rate:** From 300 to 600 g/m² according to coating.

V Precautions for Safe Handling & Use:

- 1. Protection of surfaces:** do not apply to PVC, aluminium, zinc, rubber, plastic tiles, polystyrene.
- 2. Protection of personnel:** Avoid contact with eyes and skin. Do not inhale fumes. This product has a highly corrosive action on the skin and can cause serious burns. Therefore, boots, eye protection, neoprene gloves and suitable protective clothing must be worn. In case of contact with the skin, wash immediately and abundantly with water and seek medical attention without delay.

VI Cleaning of tools:

Clean tools in water immediately after use.

VII Packaging, palletising, storage:

- 25 kg: pallet of 24 X 25 kg.
 - 6 kg: carton of 4 X 6 kg.
 - 0.9 kg: carton of 12 X 0.9 kg.
- Store the product in a cool dry place and out of direct sunlight.

Important: The contents of this documentation result from our experience of the product. We cannot be held responsible for its use in each individual case. It is essential to test areas to be treated beforehand.

SCALP E49a Created: October 1997/1198 Updated: January 2005



8 - 14, ALLÉE DE BRUXELLES - Z.I. DE LA POUDRETTE - 93320 PAVILLONS SOUS BOIS
TÉL. : 01 48 48 39 76 - FAX : 01 48 49 80 36 - E - mail : scalp@scalp-france.fr
S.A. AU CAPITAL DE 115 500 € - R.C. BOBIGNY B 562 112 227 - C.C.P. PARIS 2727-780 - SITE internet : www.scalp-france.fr