



**PRODUITS CHIMIQUES  
SPECIAUX**

## SCALPFUGE ACRYL

High performance, **film forming**, water repellent especially for roofs - acrylic silicone resin, polysiloxane resin and silane based. Extremely sophisticated water based product.

### I Applications:

**SCALPFUGE ACRYL is designed to protect roofs in tiles, slates, concrete, cement, fibro-cements, shingle, etc.** SCALPFUGE ACRYL can also be applied to walls and façades. SCALPFUGE ACRYL produces a satin appearance.

### II Product Advantages:

- Extremely sophisticated product
- Hardens and forms a protective film
- Limits frost damage
- Does not change surface porosity
- Can be applied to slightly damp surfaces
- Easy and rapid impregnation of material pores
- Stops grime and limits the formation of micro-organisms (mosses, algae, lichens, moulds) on roofs
- No special labelling required according to regulations in force for use and transport
- Contains no solvents
- Micro-porous
- Odourless
- Can be painted
- Ecological

### III Physicochemical Properties:

- Water based product
- Milky liquid
- Density: 1 g/cm<sup>3</sup> at 20°C
- PH: 12
- Not frost resistant
- Flash Point: None

### IV Instructions for use:

1. Dilution: Ready to use, never dilute.
2. Tools: Roller, manual sprayer, airless spray gun.
3. Method: Mix SCALPFUGE ACRYL well then apply to the surface to be treated, from the base upwards until the surface is saturated. Apply one or two coats depending on porosity without overuse at one hour intervals. Avoid overuse of the product, which could leave coloured traces on the surface. Apply SCALPFUGE ACRYL to clean and preferably dry surfaces.
4. Application Time: Water repellent treatment will be effective immediately on complete drying of SCALPFUGE ACRYL (one to several hours).
5. Application Temperature: From 5 to 50°C. Efficacy is reduced at extreme temperatures.
6. Application Rate: Environ 300g/m<sup>2</sup> for two coats according to materials and their porosity.

### V Precautions for Safe Handling & Use:

1. Protection of surfaces: Protect surfaces not to be treated (glass, PVC, etc.)
2. Protection of personnel: Avoid contact with eyes and skin. In case of contact, immediately wash with water.

### VI Cleaning of tools:

Clean tools in water immediately after use.

### VII Packaging, palletising, storage: Store in a frost free place

- In containers of 200 litres.
- 20 litres: pallet of 24 X 20 litres
- 5 litres: carton of 4 X 5 litres

**Important:** The contents of this documentation result from our experience of the product. We cannot be held responsible for its use in each individual case. It is essential to test areas to be treated beforehand.

SCALP E49a

Created: September 2005

Updated: September 2005



8 - 14, ALLÉE DE BRUXELLES - Z.I. DE LA POUDRETTE - 93320 PAVILLONS SOUS BOIS  
TÉL. : 01 48 48 39 76 - FAX : 01 48 49 80 36 - E - mail : [scalp@scalp-france.fr](mailto:scalp@scalp-france.fr)  
S.A. AU CAPITAL DE 115 500 € - R.C. BOBIGNY B 562 112 227 - C.C.P. PARIS 2727-780 - SITE internet : [www.scalp-france.fr](http://www.scalp-france.fr)