



**PRODUITS CHIMIQUES
SPECIAUX**

SCALPIK DECAP SEC 77

High performance liquid stripper for paints, stains, varnishes. Forms a dry residue, no rinsing required.

I Applications:

Strips stains, paints, varnishes, thin films from surfaces such as: wood, stone, concrete, iron, zinc, galvanized materials, etc.

II Product Advantages:

- No rinsing necessary
- Dry residues
- Effective and fast
- Can be repainted immediately after brushing or scratching
- Can be used for soaking
- Adheres to vertical surfaces
- Does not blacken wood
- Can be sprayed

III Physicochemical Properties:

- Methylene chloride based product
- Colourless to slightly yellowish liquid
- Density: 1.22 g/cm³ at 20°C
- PH: 10
- Frost resistant
- Flash Point: Non-flammable

IV Instructions for use:

1. Dilution: Ready to use.
2. Tools: Special sprayer (on sale at SCALP SA), roller or brush
Could be sprayed with an airless spray gun.
3. Method: Agitate well before use, then apply to the surface. Clean and scrape any dry residues. This product does not require any rinsing. The surface can be recoated immediately after scraping (ensure surface is fully dry).
4. Application Time: From 1 to 10 minutes according to the type of coating.
5. Application Temperature: From 5 to 50°C. Efficacy is reduced at extreme temperatures.
Avoid applying to wet surfaces.
6. Application Rate: From 150 to 300 g/m² according to coating.

V Precautions for Safe Handling & Use:

1. Protection of surfaces: do not apply to PVC, rubber, plastic tiles, polystyrene.
2. Protection of personnel: Avoid contact with eyes and skin. In case of contact, immediately wash with water. Do not inhale fumes. Wear gloves.

VI Cleaning of tools:

Wipe tools with a cloth after use.

VII Packaging, palletising, storage:

- 25 kg: pallet of 24 X 25 kg
- 6 kg: carton of 4 X 6 kg
- 0.9 kg: carton of 12 X 0.9 kg

Store the product in a cool dry place and out of direct sunlight.

Carton of 20 sprayer units available.

Important: The contents of this documentation result from our experience of the product. We cannot be held responsible for its use in each individual case. It is essential to test areas to be treated beforehand.

SACALP E49a

Created: October 1998/1277

Updated: January 2005



8 - 14, ALLÉE DE BRUXELLES - Z.I. DE LA POUDRETTE - 93320 PAVILLONS SOUS BOIS
TÉL. : 01 48 48 39 76 - FAX : 01 48 49 80 36 - E - mail : scalp@scalp-france.fr
S.A. AU CAPITAL DE 115 500 € - R.C. BOBIGNY B 582 112 227 - C.C.P. PARIS 2727-780 - SITE internet : www.scalp-france.fr