



**PRODUITS CHIMIQUES  
SPECIAUX**

## **SCALPNET BIO 03**

Ecological concentrated food contact quality, degreaser, and detergent, for synthetic, mineral surfaces used in building, industry and community buildings.

### **I Applications:**

This product has been designed for the cleaning and degreasing of all synthetic surfaces met in buildings such as PVC, painted surfaces (paint detergent), aluminium profiles, zinc, brass, galvanized materials, and plastic tarpaulins. It is perfectly suitable for daily cleaning of tiled mineral surfaces, glazed stone finishes, etc. It can be used as an industrial detergent for mechanical parts, generator motors etc.

### **II Product Advantages:**

- Strong degreasing power
- Highly concentrated, odourless, no rinsing required,
- Does not affect building materials
- No special labelling required according to regulations in force
- Highly versatile
- Fast action
- Food contact quality

### **III Physicochemical Properties:**

- Aqueous liquid
- Not frost resistant, but effect reversible
- Density: 1.06 g/cm<sup>3</sup> at 20°C
- PH: 12.5
- Fluorescent yellow liquid
- Flash Point: Non-flammable

### **IV Instructions for use:**

1. Dilution: From 5 to 50% depending on the amount of grime and the surface treated.
2. Tools: Sponge, cloth, sprayer, high-pressure equipment, industrial washer. For use in high-pressure machinery, we advise a concentration of the order of 1 to 5% at lance point (according to the state of the surface). For soaking applications, soak parts in the product preferably heated to 70°C. Leave to act for about twenty minutes. Remove parts, brush and rinse under running water.
3. Method: Dilute the product before application. (See below). Apply the product with a sponge then wipe the surface dry with a cloth or cotton wool. No need to rinse.
4. Application Time: Immediate.
5. Application Temperature: From 5 to 50°C. Efficacy is reduced at extreme temperatures.
6. Application Rate: According to the dilution of the product.

### **V Precautions for Safe Handling & Use:**

1. Protection of surfaces: Does not present any particular dangers to materials.
2. Protection of personnel: The product is a skin irritant so the wearing of gloves and eye protection is advised. In case of contact with eyes and skin, wash with water.

### **VI Cleaning of tools:**

Tools should be cleaned with water.

### **VII Packaging, palletising, storage:**

- 200 L: pallet of 4 X 200 L
- 30 L: pallet of 24 X 30 L
- 5 L: carton of 4 X 5 L
- 1 L: carton of 12 X 1 L

**Important:** The contents of this documentation result from our experience of the product. We cannot be held responsible for its use in each individual case. It is essential to test areas to be treated beforehand.

SCALP E49a

Created: October 1997 /

Updated: January 2005



8 - 14, ALLÉE DE BRUXELLES - Z.I. DE LA POUDRETTE - 93320 PAVILLONS SOUS BOIS  
TÉL. : 01 48 48 39 76 - FAX : 01 48 49 80 36 - E - mail : [scalp@scalp-france.fr](mailto:scalp@scalp-france.fr)  
S.A. AU CAPITAL DE 115 500 € - R.C. BOBIGNY B 562 112 227 - C.C.P. PARIS 2727-780 - SITE internet : [www.scalp-france.fr](http://www.scalp-france.fr)