



**PRODUITS CHIMIQUES  
SPECIAUX**

## **SCALPNET BIO 37**

New generation ecological cleaner for brick, concrete, glazed stone finishes, sandstone, vitreous paste, exposed and washed aggregates, deactivated concrete facades.

### **I Applications:**

Designed for the cleaning, washing and cleansing of all mineral or high silica content surfaces, from blackening from atmospheric and urban pollution.

### **II Product Advantages:**

- Not hazardous to health or the environment
- Contains no sodium carbonate, no acid, no solvents
- No neutralization of the surface (no efflorescence)
- Does not affect aluminium, Altuglass, glass, or rubber, etc. (Tiles and windows do not need protection)
- No special labelling required according to regulations in force for use and transport
- Ecological
- Biodegradable
- Can be sprayed

### **III Physicochemical Properties:**

- Aqueous product in thixotropic gel form
- Slightly yellowish
- Density: 1.10 g/cm<sup>3</sup> at 20°C
- PH: 8.5
- Not frost resistant, but effects reversible
- Flash Point: Non-flammable

### **IV Instructions for use:**

1. Dilution: Never dilute.
2. Tools: Roller, brush (all types), airless spray gun or other sprayer.
3. Method: Mix the product well before application. Apply thickly to the surface then leave to act. Rinse from the base upwards with water under pressure (cold or hot). Renew the operation as necessary.
4. Application Time: One to several hours. We advise applying in the evening and rinsing the following day.
5. Application Temperature: From 5 to 50°C. Efficacy is reduced at extreme temperatures.
6. Application Rate: From 100 to 200 g/m<sup>2</sup> according to surface porosity.

### **V Precautions for Safe Handling & Use:**

1. Protection of surfaces: No particular recommendations.
2. Protection of personnel: This product is not dangerous, but avoid contact with eyes and skin. In case of contact, wash with water.

### **VI Cleaning of tools:**

Clean tools in water immediately after use.

### **VII Packaging, palletising, storage:**

- 20 kg: pallet of 24 X 20 kg
- 5 kg: carton of 4 X 5 kg

**Important:** The contents of this documentation result from our experience of the product. We cannot be held responsible for its use in each individual case. It is essential to test areas to be treated beforehand.

SCALP E49a

Created: April 2001/1337

Updated: April 2005



8 - 14, ALLÉE DE BRUXELLES - Z.I. DE LA POUDRETTE - 93320 PAVILLONS SOUS BOIS  
TÉL. : 01 48 48 39 76 - FAX : 01 48 49 80 36 - E - mail : scalp@scalp-france.fr  
S.A. AU CAPITAL DE 115 500 € - R.C. BOBIGNY B 582 112 227 - C.C.P. PARIS 2727-780 - SITE internet : www.scalp-france.fr