



**PRODUITS CHIMIQUES
SPECIAUX**

AQUAFUGE 18

Silicone water based water repellent, providing high power protection for all surfaces, ideal for blue granite.

I Applications:

AQUAFUGE 18 is designed for walls and façades in: limestone, blue granite, concrete, cement, fibro-cement, lime, etc.

II Product Advantages:

- Extremely sophisticated product
- Highly pronounced beading effect
- Limits frost damage
- Ideal for blue granite
- Changes neither appearance nor surface porosity
- Can be applied to slightly damp surfaces
- Easy and rapid impregnation of material pores
- Prevents the build up of grime on surfaces and limits the formation of micro-organisms
- Contains no solvents
- Micro-porous
- Odourless
- Colourless
- Can be sprayed

III Physicochemical Properties:

- Water based product
- Colourless liquid
- Density: 1 g/cm³ at 20°C
- PH: 12.3
- Not frost resistant
- Flash Point: None

IV Instructions for use:

1. Dilution: Ready to use, do not dilute.
2. Tools: Roller, manual sprayer, airless spray gun.
3. Method: Mix AQUAFUGE 18 well then apply to the surface to be treated from the base upwards until saturation. Apply one or two coats at 10-minute intervals. Avoid overuse of the product, which could leave coloured traces on the surface. Apply AQUAFUGE 18 on clean and preferably dry surfaces.
4. Application Time: AQUAFUGE 18 is a permeating solution. The treatment will be effective immediately on complete drying of AQUAFUGE 18 (one to several hours).
5. Application Temperature: From 5 to 50°C. Efficacy is reduced at extreme temperatures.
6. Application Rate: According to materials and their porosity.

V Precautions for Safe Handling & Use:

1. Protection of surfaces: Protect surfaces that are not to be treated (Glass, aluminium, zinc, galvanised materials, etc.).
2. Protection of personnel: Avoid contact with eyes and skin. In case of contact, immediately wash with water.

VI Cleaning of tools:

Clean tools in water immediately after use.

VII Packaging, palletising, storage: Store in a frost free place

- In containers of 200 litres
- 20 litres: pallet of 24 X 20 litres
- 5 litres: carton of 4 X 5 litres

Important: The contents of this documentation result from our experience of the product. We cannot be held responsible for its use in each individual case. It is essential to test areas to be treated beforehand.
SCALP E49a Created: September2004 Updated: September 2005



8 - 14, ALLÉE DE BRUXELLES - Z.I. DE LA POUDRETTE - 93320 PAVILLONS SOUS BOIS
TÉL : 01 48 48 39 76 - FAX : 01 48 49 80 36 - E - mail : scalp@scalp-france.fr
S.A. AU CAPITAL DE 115 500 € - R.C. BOBIGNY B 562 112 227 - C.C.P. PARIS 2727-780 - SITE internet : www.scalp-france.fr