



**PRODUITS CHIMIQUES  
SPECIAUX**

## **SCALP ANTI-TACHE 07**

High performance water repellent, oil repellent - non-film forming in water phase with acrylic fluorinated resin base.

### **I Applications:**

SCALP ANTI-TACHE 07 is designed for use on porous materials for protection against the penetration of oil, grease, fat, wine, coffee, tannin, etc., on mainly horizontal surfaces such as interlocking paving stones, unsealed floor tiles, reconstituted stones, marble, concrete, cement, natural stones.

### **II Product Advantages:**

- Highly effective
- Odourless
- Non-flammable
- Prevents the build up of grime on surfaces and limits the formation of micro-organisms
- Micro-porous
- Easy and rapid impregnation of material pores
- No special labelling required, not hazardous to health or the environment
- Produces a beading effect
- Contains no solvents

### **III Physicochemical Properties:**

- Water based product
- Transparent, yellowish liquid
- Density: 1 g/cm<sup>3</sup> at 20°C
- PH: 7, neutral,
- Not frost resistant
- Flash Point: None

### **IV Instructions for use:**

1. Dilution: Ready to use, never dilute.
2. Tools: Roller, manual sprayer, airless spray gun.
3. Method: Mix SCALP ANTI-TACHE 07 well then apply to the surface to be treated (from the base upwards in the case of a vertical surface). Apply two coats at 10-minute intervals. Avoid overuse of the product, which could leave coloured traces on the surface. Apply SCALP ANTI-TACHE 07 on clean and preferably dry surfaces.
4. Application Time: N/A SCALP ANTI-TACHE 07 permeates the surface thoroughly. The treatment will be effective immediately on complete drying of SCALP ANTI-TACHE 07 (one to several hours).
5. Application Temperature: From 5 to 50°C. Efficacy is reduced at extreme temperatures.
6. Application Rate: According to materials and their porosity.

### **V Precautions for Safe Handling & Use:**

1. Protection of surfaces: Protect surfaces that are not to be treated.
2. Protection of personnel: Avoid contact with eyes and skin. In case of contact, immediately wash with water.

### **VI Cleaning of tools:**

Clean tools in water immediately after use.

### **VII Packaging, palletising, storage:**

- 20 litres: pallet of 24 X 20 litres
- 5 litres: carton of 4 X 5 litres

**Important:** The contents of this documentation result from our experience of the product. We cannot be held responsible for its use in each individual case. It is essential to test areas to be treated beforehand.

SCALP E49a

Created: July 2000/1207

Updated: February 2005



8 - 14, ALLÉE DE BRUXELLES - Z.I. DE LA POUDRETTE - 93320 PAVILLONS SOUS BOIS  
TÉL : 01 48 48 39 76 - FAX : 01 48 49 80 36 - E - mail : [scalp@scalp-france.fr](mailto:scalp@scalp-france.fr)  
S.A. AU CAPITAL DE 115 500 € - R.C. BOBIGNY B 582 112 227 - C.C.P. PARIS 2727-780 - SITE internet : [www.scalp-france.fr](http://www.scalp-france.fr)