



**PRODUITS CHIMIQUES
SPECIAUX**

SCALPFUGE 32

Effective and definitive barrier against capillary rising damp. Curative and preventive.

I Applications:

SCALPFUGE 32 is an injection product used for damp proofing treatment of porous building materials and for the **treatment of capillary rising damp**.

II Product Advantages:

- Highly sophisticated product
- Recognized efficacy on mineral surfaces
- Limits frost damage
- Colourless
- Water based product
- Can be applied to slightly damp surfaces
- Easy and rapid impregnation of material pores
- Odourless
- Rapid results
- Contains no solvents
- Micro-porous
- Curative and preventive
- Changes neither appearance nor surface porosity
- Can be applied in occupied premises

III Physicochemical Properties:

- Silicone derivative based aqueous product
- Colourless liquid
- Density: 1.05 g/cm³ at 20°C
- PH: 13
- Not frost resistant (effect reversible).
- Flash Point: None

IV Instructions for use:

1. Dilution: SCALPFUGE 32 is ready to use, do not dilute.
2. Tools: Masonry drill plus low-pressure injection equipment.
3. Method: Drill 14 mm diameter approx. holes in the base of the wall. Drill obliquely and if possible into vertical courses at 15 cm above ground level. Holes should be approx. 15 cm apart and $\frac{3}{4}$ of the depth of the wall.
4. Application Time: Once SCALPFUGE 32 is applied, it will be effective within approximately 48 hours.
5. Application Temperature: From 5 to 50°C. Efficacy is reduced at extreme temperatures.
6. Application Rate: 1 to 2 litres per metre, per 10 cm thickness of wall.

V Precautions for Safe Handling & Use:

1. Protection of surfaces: Protect surfaces not to be treated. (Glass, aluminium, zinc, galvanised materials, etc.).
2. Protection of personnel: Avoid contact with eyes and skin. In case of contact, immediately wash with water.

VI Cleaning of tools:

Clean tools in water immediately after use.

VII Packaging, palletising, storage: Store in a frost free place

- In containers of 200 litres
- 20 litres: pallet of 24 X 20 litres
- 5 litres: carton of 4 X 5 litres

Important: The contents of this documentation result from our experience of the product. We cannot be held responsible for its use in each individual case. It is essential to test areas to be treated beforehand.

SCALP E49a

Created: September2004/

Updated: Janvier2005



8 - 14, ALLÉE DE BRUXELLES - Z.I. DE LA POUDRETTE - 93320 PAVILLONS SOUS BOIS
TÉL : 01 48 48 39 76 - FAX : 01 48 49 80 36 - E - mail : scalp@scalp-france.fr
S.A. AU CAPITAL DE 115 500 € - R.C. BOBIGNY B 562 112 227 - C.C.P. PARIS 2727-780 - SITE internet : www.scalp-france.fr