



SCALPFUGE 35

Highly sophisticated aqueous water repellent - non-film forming polysiloxane and silane resin based.

I Applications:

SCALPFUGE 35 is a water repellent treatment for thick plasticized coatings, hydraulic coatings, stones, bricks, marble, concrete, tiles, slates, fibro-cement, blue granite, lime coatings.

II Product Advantages:

- Highly sophisticated product
- Highly pronounced beading effect
- Limits damage from frost
- Ecological
- Changes neither the appearance nor the porosity of the surface
- Can be applied to slightly damp surfaces
- Easy and fast impregnation of material pores
- Prevents the build up of grime on surfaces and limits the formation of micro-organisms
- No safety labelling required, not hazardous to health or the environment
- Contains no solvents
- Micro-porous
- Odourless
- Can be sprayed

III Physicochemical Properties:

- Aqueous product
- White liquid
- Density: 1 g/cm³ at 20°C
- PH: 7, neutral,
- Not frost resistant
- Flash Point: None

IV Instructions for use:

1. Dilution: Ready to use, never dilute.
2. Tools: Roller, manual sprayer, airless spray gun.
3. Method: Mix SCALPFUGE 35 well then apply to the surface to be treated, from the base upwards until the surface is saturated. Apply one or two coats at 10-minute intervals. Avoid overuse of the product, which could leave coloured traces on the surface. Apply SCALPFUGE 35 to clean and preferably dry surfaces.
4. Application Time: SCALPFUGE 35 is a permeating product. Water repellent treatment will be effective immediately on complete drying of SCALPFUGE 35 (one to several hours).
5. Application Temperature: From 5 to 50°C. Efficacy is reduced at extreme temperatures.
6. Application Rate: According to materials and their porosities.

V Precautions for Safe Handling & Use:

1. Protection of surfaces: Protect surfaces that are not to be water repellent treated (glass, PVC, etc.).
2. Protection of personnel: Avoid contact with eyes and skin. In case of contact, immediately wash with water.

VI Cleaning of tools:

Clean tools in water immediately after use.

VII Packaging, palletising, storage:

- 20 litres: pallet of 24 X 20 litres
- 5 litres: carton of 4 X 5 litres

Important: The contents of this documentation result from our experience of the product. We cannot be held responsible for its use in each individual case. It is essential to test areas to be treated beforehand.

SCALP E49a

Created: September 2004 /

Updated: January 2005

Page 2 1