



**PRODUITS CHIMIQUES  
SPECIAUX**

## **SCALPFUGE OM 70**

Solvented water repellent - non-silicone, non-film forming, organic-metallic compounds based.

### **I Applications:**

SCALPFUGE OM 70 is designed for the water repellent treatment of stones, plaster, hydraulic coatings, cement, concrete, brick, marble, tiles, slates, fibro-cement.

### **II Product Advantages:**

- Highly sophisticated product
- Effective on plaster
- SCALPFUGE OM 70 can be painted
- Micro-porous, facilitating the free exchange of water vapour
- Contains no silicone
- Can be sprayed
- Easy and rapid impregnation of material pores
- Produces a beading effect

### **III Physicochemical Properties:**

- Solvented product
- Transparent Colourless liquid
- Density: 0.77 g/cm<sup>3</sup> at 20°C
- PH: None
- Frost resistant
- Flash Point: 38°C closed container

### **IV Instructions for use:**

1. Dilution: Ready to use. Never dilute.
2. Tools: Natural fibre roller, manual sprayer.
3. Method: Mix the product well before use; apply to the surface to be treated from the base upwards until total saturation of the surface. Renew the operation a second time after about 20 minutes. Avoid overuse of the product, which could leave coloured traces on the surface. Apply the product to clean and dry surfaces.
4. Application Time: This is a permeating solution. Water repellent treatment will be effective immediately after the evaporation of solvents (after about 72 hours).
5. Application Temperature: From 5 to 50°C. Efficacy is reduced at extreme temperatures.
6. Application Rate: According to materials and their porosity: about 300 g/m<sup>2</sup> for both coats.

### **V Precautions for Safe Handling & Use:**

1. Protection of surfaces: do not apply the product to organic coatings (thick and medium plasticized paints, etc.). Protect surfaces that are not to be water repellent treated (glass, PVC, etc.).
2. Protection of personnel: Avoid contact with eyes and skin. In case of contact, immediately wash with water. Work in well-ventilated conditions Do not smoke.

### **VI Cleaning of tools:**

Clean tools in white spirit immediately after use.

### **VII Packaging, palletising, storage:**

- 30 litres: pallet of 24 X 30 litres
- 5 litres: carton of 4 X 5 litres

**Important:** The contents of this documentation result from our experience of the product. We cannot be held responsible for its use in each individual case. It is essential to test areas to be treated beforehand.

SCALP E49a

Created: July 2000/1170

Updated: January 2005



8 - 14, ALLÉE DE BRUXELLES - Z.I. DE LA POUDRETTE - 93320 PAVILLONS SOUS BOIS  
TÉL : 01 48 48 39 76 - FAX : 01 48 49 80 36 - E - mail : scalp@scalp-france.fr  
S.A. AU CAPITAL DE 115 500 € - R.C. BOBIGNY B 582 112 227 - C.C.P. PARIS 2727-780 - SITE internet : www.scalp-france.fr