



**PRODUITS CHIMIQUES
SPECIAUX**

SCALP PROTEC WA 67

Matt finish, colourless renewable, sacrificial anti-graffiti protection - ecological vegetal wax based.

I Applications:

PROTEC SCALP WA 67 is designed for anti-graffiti protection of all surfaces with the exception of non anti-corrosion treated metallic surfaces.

II Product Advantages:

- Very easy to apply
- Versatile (very wide variety of surfaces)
- Micro-porous and water repellent product
- Effective for inside and outside
- Does not yellow.
- Invisible film (according to surface)
- Can be sprayed
- Removal of graffiti with hot water (90°C) and under pressure.
- Ecological product
- Biodegradable
- Contains no solvents
- Non-flammable
- Odourless
- Resists U.V.

III Physicochemical Properties:

- Vegetable wax based product in emulsion
- Milky liquid.
- Density: 1g/cm³ at 20°C
- PH: 9
- Not frost resistant
- Flash Point: Non-flammable

IV Instructions for use:

1. Dilution: SCALP PROTEC WA 67 is ready to use.
2. Tools: Roller (lacquer), sprayer (airless spray gun).
3. Method: Mix the product well before application. Apply SCALP PROTEC WA 67 to a clean dry surface in two crossed coats (at about 2 hours interval according to outside temperature). Avoid over-colouring and overuse.
Removal of the graffiti: Graffiti will be effectively removed with hot water (90°C at 30 bar minimum). The protection and the graffiti will be removed; therefore the protection will need to be renewed.
4. Application Time: About 2 hours according to climatic conditions and surface.
5. Application Temperature: From 5 °C to 50 °C. Efficacy is reduced at extreme temperatures.
6. Application Rate: From 150 to 200 g/m² according to the coating and for the 2 coats.

V Precautions for Safe Handling & Use:

1. Protection of surfaces: Avoid contact with all surfaces that are not to be protected.
2. Protection of personnel: This product is not dangerous but avoid contact with eyes and skin.

VI Cleaning of tools:

Clean tools in hot water immediately after use.

VII Packaging, palletising, storage:

- 5 litres: carton of 4 X 5 litres
- 20 litres: pallet of 24 X 20 litres

Important: The contents of this documentation result from our experience of the product. We cannot be held responsible for its use in each individual case. It is essential to test areas to be treated beforehand.

Scalp E49a Created: February 2001/132 Updated: January 2005